

1 2 3 4 5 6 7 8


TECHNICAL SHEET


FARMER SCREW GALVANIZED STEEL

UNI-FSK









Correct setting of the tightening torque when anchoring the screws:

- A correctly set tightening torque (flat washer, compressed seal slightly rounded around the circumference)
- **B** high tightening torque (EPDM seal excessively deformed, possibility of cracking and subsequent loss of tightness)
- C small tightening torque (washer with EPDM seal does not have sufficient sealing ability)

Place of use:

- $\boldsymbol{\mathsf{A}}$ use in the upper part of the wave
- B use in the lower part of the metal sheet
- C use for metal sheet metal sheet connection

Dimensions [mm]								
Nominal dimension	L							
4,8 x 20	20							
4,8 x 35	35							
4,8 x 60	60							



SK Galvanized steel prepainted – Ivory – RAL 1015

INDEX	CHANGE		DATE	SIGNATURE		KJG QUALITY ®	Scan code for 3D model	
MATERIAL BRAND W.C.					WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS								
AUXILIARY EQUIPMENT					STN STANDARD		SORTING NUMBER	
ELABORATED BY Ing. Kluska M.				NOTE		POSITION NUMBER		
TEST	TED BY				1			
TECHNOLOGIST TECHNOLOGIST				OLD DRAWING		DRAWING NUMBER		
NAME Farmer screw galvanized steel					Number of she	UNI-	FSK	Sheet A

Created: 03.12.2025 18:13:49

Technical changes reserved

1 2 3 4 5 6 7 8