

1 2 3 4 5 6 7 8


TECHNICAL SHEET

SELF-DRILLING SCREW GALVANIZED STEEL GT5

UNI-GT 5







Technical parameters:





















RAL powder.coat

Correct setting of the tightening torque when anchoring the screws:

- A correctly set tightening torque (flat washer, compressed seal slightly rounded around the circumference)
- **B** high tightening torque (EPDM seal excessively deformed, possibility of cracking and subsequent loss of tightness)
- C small tightening torque (washer with EPDM seal does not have sufficient sealing ability)

Heer

 self-drilling screws for fixing profiled structural steel sheets to thin-walled steel structures

Dimensions [mm]									
Nominal dimension	L								
5,5 x 19	19								
5,5 x 25	25								
5,5 x 32	32								



OC Galvanized steel prepainted – Steel red – RAL 3009

INDEX	CHANGE		DATE	SIGNATURE		KJG QUALITY ®		Scan code for 3D model	
MATERIAL BRAND W.C.					WEIGHT kg		SCALE		
SIZE, SEMI-FINISHED PRODUCTS									
AUXILIARY EQUIPMENT					STN STANDARD SO		SORTI	NG NUMBER	
ELABORATED BY Ing. Kluska M.					NOTE		POSIT	POSITION NUMBER	
TESTED BY									
TECHNOLOGIST TECHNOLOGIST				OLD DRAWING		DRAWING NUMBER			
NAME Self-drilling screw galvanized steel GT5				Number of she	UNI-	GT 5	Sheet		

Created: 03.12.2025 18:13:52

Technical changes reserved

1 2 3 4 5 6 7 8