1 2 3 4 5 6 7 8

TECHNICAL SHEET

ENKE ENKOPUR GRAY

Enkopur is a single-component polyurethane layer based on proven PUR - prepolymers, which is resistant to weather influences. The chemical composition is based on liquid polyurethane resin.

Enkopur MUST NOT be diluted with water UNDER ANY CIRCUMSTANCES!!!

ENKOPUR liquid foil with a polyester mat insert (Polyflexvlies - also available in the offer) turns into an elastic rubber-like membrane after application. This "layer" is resistant to atmospheric conditions.

Enkopur is used as a waterproofing layer without cracks. Seals all types of problematic places and roof penetrations.


LONG-TERM PROTECTION OF SURFACES against moisture, creates, on the other hand, a coating with perfect vapour permeability (does not retain moisture inside!!! – after time, building materials may naturally dry out).

Enkopur is a seamless, highly elastic, vapour-permeable and weather-resistant sealing system, which in conjunction with the polyester mat Enke-Polyflexvlies is a long-proven system for sealing roofs, connections and penetrations. It is suitable not only for old, weathered, asphalt roof surfaces, but also for foil and metal roofs, especially in areas where long-term stagnant water can occur, e.g. in roof gutters or water exchange areas.

APPLICATION:







Technical parameter					
Composition	polyurethane resin				
Colour	silver-grey				
Operating temperature	+5°C up to +30°C				
Hardening	3–4 days at minimum temperature of 10 °C				
Consumption	min. 3 kg/m²				
Weight	4 kg / 12,5 kg / 25 kg				

SCH-ENKE ENKO



PS

Dusty grey

UNDEX OHANGE	DATE	SIGNATURE	-	KJG QUALITY ®	
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS					
AUXILIARY EQUIPMENT			STN STANDARD	SORTING NUMBER	
ELABORATED BY Ing. Kluska M.			NOTE	POSITION NUMBER	
TESTED BY					
TECHNOLOGIST	TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER	
NAME Enke Er	nkopur gray		Number of sheets	ENKE ENKO Sheet	Å

Created: 03.12.2025 21:36:04

Technical changes reserved

1	2	3	4	5	6	7	8