

TECHNICAL SHEET

ENKE ENKOPUR BLACK

Enkopur is a single-component polyurethane layer based on proven PUR - prepolymers, which is resistant to weather influences. The chemical composition is based on liquid polyurethane resin.

Enkopur MUST NOT be diluted with water UNDER ANY CIRCUMSTANCES!!!


ENKOPUR liquid foil with a polyester mat insert (Polyflexvlies - also available in the offer) turns into an elastic rubber-like membrane after application. This „layer“ is resistant to atmospheric conditions.

Enkopur is used as a waterproofing layer without cracks. Seals all types of problematic places and roof penetrations.

LONG-TERM PROTECTION OF SURFACES against moisture, creates, on the other hand, a coating with perfect vapour permeability (does not retain moisture inside!!! – after time, building materials may naturally dry out).

Enkopur is a seamless, highly elastic, vapour-permeable and weather-resistant sealing system, which in conjunction with the polyester mat Enke-Polyflexvlies is a long-proven system for sealing roofs, connections and penetrations. It is suitable not only for old, weathered, asphalt roof surfaces, but also for foil and metal roofs, especially in areas where long-term stagnant water can occur, e.g. in roof gutters or water exchange areas.

APPLICATION:



Technical parameter	
Composition	polyurethane resin
Colour	black
Operating temperature	+5 °C up to +30 °C
Hardening	3–4 days at minimum temperature of 10 °C
Consumption	min. 3 kg/m ²
Weight	12,5kg

SCH-ENKE.ENKO



IC Intense black

INDEX	CHANGE	DATE	SIGNATURE	KJG
				QUALITY ®
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS				
AUXILIARY EQUIPMENT		STN STANDARD	SORTING NUMBER	
ELABORATED BY Ing. Kluska M.		NOTE	POSITION NUMBER	
TESTED BY				
TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER	
NAME		Enke Enkopur black		
		Number of sheets		SCH-ENKE.ENKO
				Sheet

Created: 19.01.2026 18:48:19

Technical changes reserved