

TECHNICAL SHEET

# ENKE PLASTIC BLACK SEALANT AND BITUMEN ADHESIVE

**Enkolit** is a permanently plastic adhesive and sealing compound on a bitumen base, which enables easy bonding window ledge and attic sheet metals. With the help of ENKOLIT, you can also glue leeward strips, waterbars and various flashing.

**Enkolit** is used for bonding and sealing metal profiles or sheets (e.g. titanium-zinc, copper, aluminium, stainless steel, etc.) to other building materials. The achieved strength corresponds to DIN 1055 "Design loads for building (wind load)" which can be proven on bonded joints up to 30 years old.

**Enkolit** has excellent adhesion to masonry, concrete, zinc, titanium zinc, copper, aluminium, steel, wood, veneered wood, natural or artificial stone, fibre cement, slate, OSB boards.

**Enkolit** protects the sheet against corrosion attack by moisture on the underside.

**Enkolit** is resistant to industrial fumes, salt water, root growth and is fungicidal (destroys fungi and moulds).

**APPLICATION:**



Technical parameter	
Composition	plastic screed and bituminous mass
Colour	black
Operating temperature	+ 5 °C to + 40 °C
Storability	area with a higher temperature
Consumption	approx. 2–3 kg/m <sup>2</sup> , max. 5 kg/m <sup>2</sup>
Density	approx. 1,1 kg/m <sup>2</sup> at 20 °C
Weight	11 kg

# SCH-ENKS ENKOLIT



**IC** Intense black

INDEX CHANGE	DATE	SIGNATURE		
MATERIAL BRAND			STN STANDARD	
SIZE, SEMI-FINISHED PRODUCTS			SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE	
ELABORATED BY Ing. Kluska M.			POSITION NUMBER	
TESTED BY			DRAWING NUMBER	
TECHNOLOGIST			OLD DRAWING	
NAME			DRAWING NUMBER	
Enke plastic black sealant and bitumen adhesive			SCH-ENKS ENKOLIT	
Number of sheets			Sheet 	

Created: 21.04.2026 17:27:34

Technical changes reserved