

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**

- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C00 TRAN** Transparent

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Transparent
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	Scan code for 3D model
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS				
AUXILIARY EQUIPMENT			STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.			NOTE	POSITION NUMBER
TESTED BY				
TECHNOLOGIST		TECHNOLOGIST	OLD DRAWING	DRAWING NUMBER
NAME Transparent premium silicone 310 ml			Number of sheets	SCH-OTTOSEAL S110 Sheet

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**

- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C49 TM** Testa di Moro

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Testa di Moro
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	Scan code for 3D model
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS				
AUXILIARY EQUIPMENT			STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.			NOTE	POSITION NUMBER
TESTED BY				
TECHNOLOGIST	TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER
NAME Transparent premium silicone 310 ml			Number of sheets	SCH-OTTOSEAL S110 Sheet

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**

- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C155 AN Anthracite**

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Anthracite
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	Scan code for 3D model
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD	SORTING NUMBER
AUXILIARY EQUIPMENT			NOTE	POSITION NUMBER
ELABORATED BY Ing. Kluska M.				
TESTED BY			OLD DRAWING	DRAWING NUMBER
TECHNOLOGIST				
NAME Transparent premium silicone 310 ml			Number of sheets	SCH-OTTOSEAL S110 Sheet

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**





- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C04 IC** Intense black

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Intense black
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	W.C.	WEIGHT kg	SCALE			
SIZE, SEMI-FINISHED PRODUCTS				NOTE	POSITION NUMBER			
AUXILIARY EQUIPMENT				ELABORATED BY Ing. Kluska M.	TECHNOLOGIST	OLD DRAWING	DRAWING NUMBER	
TESTED BY				NAME Transparent premium silicone 310 ml		Number of sheets SCH-OTTOSEAL S110 Sheet 		

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**





- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C29 OC** Steel red

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Steel red
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	W.C.	WEIGHT kg	SCALE				
									MATERIAL BRAND
SIZE, SEMI-FINISHED PRODUCTS				NOTE	POSITION NUMBER				
AUXILIARY EQUIPMENT				ELABORATED BY Ing. Kluska M.	TECHNOLOGIST	OLD DRAWING	DRAWING NUMBER		
TESTED BY				NAME		SCH-OTTOSEAL S110 Number of sheets Sheet 			
				Transparent premium silicone 310 ml					

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

# SCH-OTTOSEAL S110

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**

- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**



**C20 PS** Dusty grey

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Dusty grey
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	Scan code for 3D model
	W.C.	WEIGHT kg		
MATERIAL BRAND			STN STANDARD	
SIZE, SEMI-FINISHED PRODUCTS			SORTING NUMBER	
AUXILIARY EQUIPMENT			POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			NOTE	
TESTED BY			DRAWING NUMBER	
TECHNOLOGIST			OLD DRAWING	
NAME Transparent premium silicone 310 ml			DRAWING NUMBER SCH-OTTOSEAL S110	
			Number of sheets Sheet	

Created: 03.06.2026 23:36:13

Technical changes reserved

TECHNICAL SHEET

# TRANSPARENT PREMIUM SILICONE 310 ml

**APPLICATION:**

- glazing wooden windows
- sealing joints on wooden, metal and plastic windows and doors
- sealing double glass (e.g. „Profilit“)
- expansion and connection joints to prefabricated concrete and aerated concrete panels
- sealing facades, metal structures
- suitable for cementing glass elements
- expansion joints in sanitary facilities

**PROPERTIES:**

- excellent resistance to weathering, aging and UV radiation
- excellent initial overload resistance
- highly resistant to abrasion and expansion
- immediately resistant to rain
- good compatibility with DIN 52452 coatings (non-paintable)
- non-sticky surface
- excellent adhesion to many substrates, partly in combination with a primer
- good UV resistance
- does not cause corrosion on unprotected metal surfaces
- contains fungicides (resistance to mould attack)
- compatible with PVB foils in accordance with the criteria of the directive ift DI-02/1
- expansion value at 100 % (ISO 37, S3A): 0,4 N/mm<sup>2</sup>

**APPLICATION:**







# SCH-OTTOSEAL S110



C9010 **B** Pure white

Technical parameter	
Composition	single-component silicone sealant with neutral crosslinking, without MEKO
Colour	Pure white
Processing temperature	+5 °C to +35 °C
Hardening	24 hours ~ 2 – 3 mm (at +23 °C / 50 % RLF)
Heat resistance	-40 °C to +180 °C
Volume shrinkage (loss)	~ 7%
Total permissible deformation	25%
Creating a surface layer	~ 10 min. (at +23 °C / 50 % RLF)
Module 100%	~ 1,5 N/mm <sup>2</sup>
Storability	12 months (at +23 °C / 50 % RLF)
Cartridge volume	310 ml
Weight	0,347 kg/pcs

INDEX CHANGE	DATE	SIGNATURE			
	W.C.	WEIGHT kg			
MATERIAL BRAND			STN STANDARD		
SIZE, SEMI-FINISHED PRODUCTS			SORTING NUMBER		
AUXILIARY EQUIPMENT			NOTE		
ELABORATED BY Ing. Kluska M.			POSITION NUMBER		
TESTED BY			DRAWING NUMBER		
TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER		
NAME Transparent premium silicone 310 ml			SCH-OTTOSEAL S110		
Number of sheets			Sheet 		

Created: 03.06.2026 23:36:13

Technical changes reserved