1 2 3 4 5 6 7 8

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:

shake can vigorously for 1-2 minutes!



After use:

spray the valve is clean



Application:

2 – 3 coats, dry film thickness: 40 – 50 μm



Drying:

ready for assembly after 12 h



Flash-off time:

3 – 5 minutes



Safety:

safety datasheet

Technical parameter					
Volume	400 ml				
☐ Packaging	6 pcs/1392 pcs				

SCH-POKS





Anthracite - RAL 7016

INDEX	CHANGE		DATE	SIGNATURE		KJG QUALITY ®		Scan code for 3D model
MAT	MATERIAL BRAND W.C.			WEIGHT kg		SCALE		
SIZE	SIZE, SEMI-FINISHED PRODUCTS							
AUX	AUXILIARY EQUIPMENT				STN STANDARD		SORTING NUMBER	
ELA	ELABORATED BY Ing. Kluska M.			NOTE		POSITION NUMBER		
TES	TED BY				1			
TEC	TECHNOLOGIST TECHNOLOGIST				OLD DRAWING		DRAWING NUMBER	
NAM	NAME Paint correction spray 400 ml				Number of she	SCH-	POK	S Sheet A

Created: 03.12.2025 13:46:18

Technical changes reserved

1	2	3	4	5	6	7	8