

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:

shake can vigorously for 1–2 minutes!



After use:

spray the valve is clean



Application:

2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:

ready for assembly after 12 h



Flash-off time:

3 – 5 minutes



Safety:

safety datasheet



OC Steel red – RAL 3009

INDEX CHANGE	DATE		SIGNATURE		KJG QUALITY®	Scan code for 3D model	
MATERIAL BRAND			W.C.		WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS							
AUXILIARY EQUIPMENT					STN STANDARD	SORTING NUMBER	
ELABORATED BY Ing. Kluska M.					NOTE	POSITION NUMBER	
TESTED BY							
TECHNOLOGIST			TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER	
NAME			Paint correction spray 400 ml		Number of sheets	SCH-POKS Sheet	

Created: 04.12.2025 06:08:15

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs