

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50%
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:
shake can vigorously for 1–2 minutes!



After use:
spray the valve is clean



Application:
2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:
ready for assembly after 12 h



Flash-off time:
3 – 5 minutes



Safety:
safety datasheet



OC Steel red – RAL 3009

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS				STN STANDARD	SORTING NUMBER	
AUXILIARY EQUIPMENT				NOTE	POSITION NUMBER	
ELABORATED BY Ing. Kluska M.						
TESTED BY						
TECHNOLOGIST		TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER	
NAME				Paint correction spray 400 ml		
			Number of sheets	SCH-POKS		Sheet

Created: 22.04.2026 16:16:26

Technical changes reserved