

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:

shake can vigorously for 1–2 minutes!



After use:

spray the valve is clean



Application:

2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:

ready for assembly after 12 h



Flash-off time:

3 – 5 minutes



Safety:

safety datasheet



OC Steel red – RAL 3009

INDEX CHANGE	DATE		SIGNATURE	W.C.	WEIGHT kg	SCALE
MATERIAL BRAND					KJG QUALITY®	
SIZE, SEMI-FINISHED PRODUCTS					Scan code for 3D model	
AUXILIARY EQUIPMENT					STN STANDARD	
ELABORATED BY Ing. Kluska M.					NOTE	
TESTED BY					SORTING NUMBER	
TECHNOLOGIST					POSITION NUMBER	
NAME					DRAWING NUMBER	
Paint correction spray 400 ml					OLD DRAWING	
Number of sheets					SCH-POKS	
					Sheet	

Created: 19.01.2026 15:00:09

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs