

# TECHNICAL SHEET

## PAINT CORRECTION SPRAY 400 ml

SCH-POKS

### PRIVATE BRAND CORRECTION SPRAY KJG®

#### APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

#### IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50 %
- expiration from the date of production = 3 years

#### PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

#### APPLICATION OF CORRECTION SPRAY KJG®:



##### Preparation:

shake can vigorously for 1–2 minutes!



##### After use:

spray the valve is clean



##### Application:

2 – 3 coats,  
dry film thickness: 40 – 50 µm



##### Drying:

ready for assembly after 12 h



##### Flash-off time:

3 – 5 minutes



##### Safety:

safety datasheet



**MH** Copper brown – RAL 8004

INDEX CHANGE			DATE	SIGNATURE	<b>KJG</b> QUALITY®	Scan code for 3D model	
MATERIAL BRAND					W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS							
AUXILIARY EQUIPMENT						STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.						NOTE	POSITION NUMBER
TESTED BY							
TECHNOLOGIST					TECHNOLOGIST	OLD DRAWING	DRAWING NUMBER
NAME					Paint correction spray 400 ml		
					Number of sheets	SCH-POKS Sheet	

Created: 04.12.2025 06:07:33

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs