

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:

shake can vigorously for 1–2 minutes!



After use:

spray the valve is clean



Application:

2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:

ready for assembly after 12 h



Flash-off time:

3 – 5 minutes



Safety:

safety datasheet



BH White aluminum – RAL 9006

INDEX CHANGE	DATE		SIGNATURE	KJG QUALITY®	Scan code for 3D model	QR CODE
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS						
AUXILIARY EQUIPMENT			STN STANDARD		SORTING NUMBER	
ELABORATED BY Ing. Kluska M.			NOTE		POSITION NUMBER	
TESTED BY				OLD DRAWING		DRAWING NUMBER
TECHNOLOGIST		TECHNOLOGIST				
NAME			Paint correction spray 400 ml		Number of sheets	
					SCH-POKS	
					Sheet	

Created: 06.03.2026 00:00:18

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs