

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 40 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:**Preparation:**

shake can vigorously for 1–2 minutes!

**After use:**

spray the valve is clean

**Application:**2 – 3 coats,
dry film thickness: 40 – 50 µm**Drying:**

ready for assembly after 12 h

**Flash-off time:**

3 – 5 minutes

**Safety:**

safety datasheet

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1392 pcs



MM Metallic copper – RAL extra

INDEX	CHANGE	DATE	SIGNATURE	KJG	Scan code for 3D model
				QUALITY ®	
MATERIAL BRAND		W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS					
AUXILIARY EQUIPMENT			STN STANDARD	SORTING NUMBER	
ELABORATED BY	Ing. Kluska M.		NOTE	POSITION NUMBER	
TESTED BY					
TECHNOLOGIST	TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER	
NAME	Paint correction spray 400 ml			SCH-POKS	Sheet
				Number of sheets	

Created: 19.01.2026 18:49:13

Technical changes reserved