

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 40 %
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:

shake can vigorously for 1–2 minutes!



After use:

spray the valve is clean



Application:

2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:

ready for assembly after 12 h



Flash-off time:

3 – 5 minutes



Safety:

safety datasheet



Metallic copper – RAL extra

INDEX CHANGE			DATE	SIGNATURE		
MATERIAL BRAND			W.C.		WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS						
AUXILIARY EQUIPMENT					STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.					NOTE	POSITION NUMBER
TESTED BY						
TECHNOLOGIST			TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER
NAME			Paint correction spray 400 ml		Number of sheets	SCH-POKS Sheet

Created: 04.12.2025 04:45:28

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs