

TECHNICAL SHEET

# PAINT CORRECTION SPRAY 400 ml

# SCH-POKS

## PRIVATE BRAND CORRECTION SPRAY KJG®

**APPLICATION:**

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

**IMPORTANT:**

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 40%
- expiration from the date of production = 3 years

**PROPERTIES:**

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

**APPLICATION OF CORRECTION SPRAY KJG®:**



**Preparation:**  
shake can vigorously for 1–2 minutes!



**After use:**  
spray the valve is clean



**Application:**  
2 – 3 coats,  
dry film thickness: 40 – 50 µm



**Drying:**  
ready for assembly after 12 h



**Flash-off time:**  
3 – 5 minutes



**Safety:**  
safety datasheet



**MM** Metallic copper – RAL extra

INDEX	CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY®	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS				STN STANDARD	SORTING NUMBER
AUXILIARY EQUIPMENT				NOTE	POSITION NUMBER
ELABORATED BY Ing. Kluska M.					
TESTED BY					
TECHNOLOGIST		TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER
NAME			Paint correction spray 400 ml		Number of sheets
					SCH-POKS
					Sheet

Created: 20.04.2026 23:26:21

Technical changes reserved

Technical parameter	
Volume	400 ml
Packaging	6 pcs / 1 392 pcs