

TECHNICAL SHEET

# PAINT CORRECTION SPRAY 400 ml

# SCH-POKS

## PRIVATE BRAND CORRECTION SPRAY KJG®

**APPLICATION:**

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

**IMPORTANT:**

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50%
- expiration from the date of production = 3 years

**PROPERTIES:**

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

**APPLICATION OF CORRECTION SPRAY KJG®:**



**Preparation:**  
shake can vigorously for 1–2 minutes!



**After use:**  
spray the valve is clean



**Application:**  
2 – 3 coats,  
dry film thickness: 40 – 50 µm



**Drying:**  
ready for assembly after 12 h



**Flash-off time:**  
3 – 5 minutes



**Safety:**  
safety datasheet

| Technical parameter |                   |
|---------------------|-------------------|
| Volume              | 400 ml            |
| Packaging           | 6 pcs / 1 392 pcs |



**BHT** Grey aluminum P.20 – RAL 9007

|                              |        |              |                  |                               |                        |       |
|------------------------------|--------|--------------|------------------|-------------------------------|------------------------|-------|
| INDEX                        | CHANGE | DATE         | SIGNATURE        | <b>KJG</b><br>QUALITY®        | Scan code for 3D model |       |
|                              |        |              |                  |                               |                        |       |
| MATERIAL BRAND               |        |              | W.C.             | WEIGHT kg                     | SCALE                  |       |
| SIZE, SEMI-FINISHED PRODUCTS |        |              |                  | STN STANDARD                  | SORTING NUMBER         |       |
| AUXILIARY EQUIPMENT          |        |              |                  | NOTE                          | POSITION NUMBER        |       |
| ELABORATED BY Ing. Kluska M. |        |              |                  |                               |                        |       |
| TESTED BY                    |        |              |                  |                               |                        |       |
| TECHNOLOGIST                 |        | TECHNOLOGIST |                  | OLD DRAWING                   | DRAWING NUMBER         |       |
| NAME                         |        |              |                  | Paint correction spray 400 ml |                        |       |
|                              |        |              | Number of sheets | SCH-POKS                      |                        | Sheet |

Created: 06.06.2026 20:30:55

Technical changes reserved