

TECHNICAL SHEET

PAINT CORRECTION SPRAY 400 ml

SCH-POKS

PRIVATE BRAND CORRECTION SPRAY KJG®

APPLICATION:

- to repair small damages to the coloured surface of galvanized lacquered gutter system products KJG®

IMPORTANT:

- the colour is tuned from galvanized lacquered gutter system KJG®
- gloss 50%
- expiration from the date of production = 3 years

PROPERTIES:

- high-quality acrylic lacquer
- quick-drying
- good flow
- suitable for outdoor use
- weather-resistant
- light-resistant
- UV-resistant
- scratch-resistant

APPLICATION OF CORRECTION SPRAY KJG®:



Preparation:
shake can vigorously for 1–2 minutes!



After use:
spray the valve is clean



Application:
2 – 3 coats,
dry film thickness: 40 – 50 µm



Drying:
ready for assembly after 12 h



Flash-off time:
3 – 5 minutes



Safety:
safety datasheet

| Technical parameter | |
|---------------------|-------------------|
| Volume | 400 ml |
| 📦 Packaging | 6 pcs / 1 392 pcs |



MZ Moss green – RAL 6005

| | | | | | |
|------------------------------|--------|--------------|-------------------------------|------------------------|------------------------|
| INDEX | CHANGE | DATE | SIGNATURE | KJG QUALITY® | Scan code for 3D model |
| | | | | | |
| MATERIAL BRAND | | | W.C. | WEIGHT kg | SCALE |
| SIZE, SEMI-FINISHED PRODUCTS | | | | STN STANDARD | SORTING NUMBER |
| AUXILIARY EQUIPMENT | | | | NOTE | POSITION NUMBER |
| ELABORATED BY Ing. Kluska M. | | | | | |
| TESTED BY | | | | | |
| TECHNOLOGIST | | TECHNOLOGIST | | OLD DRAWING | DRAWING NUMBER |
| NAME | | | Paint correction spray 400 ml | | Number of sheets |
| | | | | | SCH-POKS |
| | | | | | Sheet |

Created: 04.06.2026 14:21:30

Technical changes reserved