

TECHNICAL SHEET

PAINT CORRECTION GALVANIZED STEEL 20 ml

SCH-POLAK

APPLICATION:

- to repair small damage to the painted surface of galvanized products




PROPERTIES:

- high-quality acrylic varnish
- standard shades according to the RAL standard
- fast drying
- good flow rate
- smooth and glossy surface
- suitable for indoor and outdoor use
- weather resistant
- resistant to light
- resistant to UV radiation
- resistant to scratches and impacts



MH Copper brown – RAL 8004

Technical parameter	
Density	1,024 g/cm ³
Theoretical capacity	~ 536 m ² /l/1 μm
Solids content	~ 69%
Durability	36 months
Volume	20 ml
Weight	31 g/pcs

INDEX CHANGE		DATE	SIGNATURE		
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS					
AUXILIARY EQUIPMENT				STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.				NOTE	POSITION NUMBER
TESTED BY					
TECHNOLOGIST		TECHNOLOGIST		OLD DRAWING	DRAWING NUMBER
NAME Paint correction galvanized steel 20 ml				Number of sheets	SCH-POLAK Sheet 

Created: 07.06.2026 10:22:05

Technical changes reserved