

TECHNICAL SHEET

# PAINT CORRECTION GALVANIZED STEEL 20 ml

# SCH-POLAK

**APPLICATION:**

- to repair small damage to the painted surface of galvanized products

**PROPERTIES:**

- high-quality acrylic varnish
- standard shades according to the RAL standard
- fast drying
- good flow rate
- smooth and glossy surface
- suitable for indoor and outdoor use
- weather resistant
- resistant to light
- resistant to UV radiation
- resistant to scratches and impacts



**MOT** Gentian blue – RAL 5010

Technical parameter	
Density	1,024 g/cm <sup>3</sup>
Theoretical capacity	~ 536 m <sup>2</sup> /l/1 μm
Solids content	~ 69 %
Durability	36 months
Volume	20 ml
Weight	31 g/pcs

INDEX	CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS					
AUXILIARY EQUIPMENT			STN STANDARD		SORTING NUMBER
ELABORATED BY Ing. Kluska M.			NOTE		POSITION NUMBER
TESTED BY					
TECHNOLOGIST		TECHNOLOGIST	OLD DRAWING		DRAWING NUMBER
NAME Paint correction galvanized steel 20 ml			Number of sheets		SCH-POLAK Sheet

Created: 21.04.2026 23:52:51

Technical changes reserved