

TECHNICAL SHEET

PAINT CORRECTION GALVANIZED STEEL 20 ml

SCH-POLAK

APPLICATION:

- to repair small damage to the painted surface of galvanized products

PROPERTIES:

- high-quality acrylic varnish
- standard shades according to the RAL standard
- fast drying
- good flow rate
- smooth and glossy surface
- suitable for indoor and outdoor use
- weather resistant
- resistant to light
- resistant to UV radiation
- resistant to scratches and impacts



TZ Reseda green – RAL 6011

| Technical parameter | |
|----------------------|------------------------------|
| Density | 1,024 g/cm ³ |
| Theoretical capacity | ~ 536 m ² /l/1 μm |
| Solids content | ~ 69 % |
| Durability | 36 months |
| Volume | 20 ml |
| Weight | 31 g/pcs |

| | | | | | |
|---|--------|--------------|------------------|-------------------------|------------------------|
| INDEX | CHANGE | DATE | SIGNATURE | KJG QUALITY ® | Scan code for 3D model |
| | | | | | |
| MATERIAL BRAND | | | W.C. | WEIGHT kg | SCALE |
| SIZE, SEMI-FINISHED PRODUCTS | | | | | |
| AUXILIARY EQUIPMENT | | | STN STANDARD | | SORTING NUMBER |
| ELABORATED BY Ing. Kluska M. | | | NOTE | | POSITION NUMBER |
| TESTED BY | | | | | |
| TECHNOLOGIST | | TECHNOLOGIST | OLD DRAWING | | DRAWING NUMBER |
| NAME Paint correction galvanized steel 20 ml | | | Number of sheets | | SCH-POLAK Sheet |

Created: 07.06.2026 11:02:35

Technical changes reserved