

TECHNICAL SHEET

PAINT CORRECTION GALVANIZED STEEL 20 ml

SCH-POLAK

APPLICATION:

- to repair small damage to the painted surface of galvanized products





PROPERTIES:

- high-quality acrylic varnish
- standard shades according to the RAL standard
- fast drying
- good flow rate
- smooth and glossy surface
- suitable for indoor and outdoor use
- weather resistant
- resistant to light
- resistant to UV radiation
- resistant to scratches and impacts



B Pure white – RAL 9010

Technical parameter	
Density	1,024 g/cm ³
Theoretical capacity	~ 536 m ² /l/1 µm
Solids content	~ 69 %
Durability	36 months
Volume	20 ml
Weight	31 g/pcs

INDEX CHANGE			DATE	SIGNATURE			
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS							
AUXILIARY EQUIPMENT					STN STANDARD		SORTING NUMBER
ELABORATED BY Ing. Kluska M.					NOTE		POSITION NUMBER
TESTED BY							
TECHNOLOGIST			TECHNOLOGIST		OLD DRAWING		DRAWING NUMBER
NAME			Paint correction galvanized steel 20 ml		Number of sheets		SCH-POLAK Sheet 

Created: 19.01.2026 19:30:02

Technical changes reserved