

TECHNICAL SHEET

# SIKA SEALING BITUMEN SEALANT

Sika BlackSeal®-1 is a single-component bitumen based construction sealant with good adhesion to most common construction materials.

**APPLICATION:**

- suitable for external sealing and repairing applications in exteriors, on roofs, walls and other building elements

**PROPERTIES:**

- good adhesion to many substrates
- it does not require primer/base coat
- easy to apply
- it can be applied on moist, non-porous substrates

**UPOZORNENIE:**

- it is not paintable
- do not use for joints loaded with water
- do not use for sealing glass
- do not use for sealing joints in and around swimming pools
- do not use on natural stone
- do not use in direct contact with other sealants or adhesives

# SCH-SIKA BLACKSEAL



Technical parameter	
Composition	Silicone-free joint sealant on the basis of synthetic rubber
Colour	black
Operating temperature	-20 °C to +70 °C
Fluidity	< 3 mm (20 mm profile, +23 °C)
Ambient air temperature	+5 °C up to +40 °C, min. 3 °C above due-point temperature
Substrate temperature	+5 °C to +40 °C
Storability	12 months in dry, dark areas, at a temperature of +5 °C to +25 °C
Cartridge volume	300 ml
Weight	0,445 kg/pcs

INDEX CHANGE	DATE	SIGNATURE		
MATERIAL BRAND			WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD	SORTING NUMBER
AUXILIARY EQUIPMENT			NOTE	POSITION NUMBER
ELABORATED BY Ing. Kluska M.				
TESTED BY			OLD DRAWING	DRAWING NUMBER
TECHNOLOGIST				
NAME			SCH-SIKA BLACKSEAL	
Sika sealing bitumen sealant			Number of sheets	Sheet 

Created: 14.05.2026 16:42:25

Technical changes reserved