

TECHNICAL SHEET

SIKA BITUMEN SEALING GRAY STRIP

Sika® MultiSeal is a self-adhesive, rubber-modified bitumen sealing tape, on the upper side laminated with aluminium foil.

APPLICATION:

- for sealing, insulating and repairs against moisture penetration and bonding joints on roofs, sheeting, cracks, bitumen and other roofing strips

PROPERTIES:



- very economical
- good adhesion on many substrates
- resistant to weather effects
- self-adhesive
- UV resistant
- resistant to bitumen
- paintable
- can be applied even at low temperatures

Technical parameter	
Composition	Bituminous tape modified with rubber
Dimension	100 mm x 3 m 200 mm x 3 m
Thickness	~ 1,2 mm (including aluminum foil ~ 0,05 mm)
Colour	upper side: aluminium foil, matt grey lower side: self-adhesive black bitumen tape protected by film
Fire resistance class	B2 according to DIN 4102
Tensile strength	longitudinal ~ 3,6 N/mm ² , transverse ~ 3,5 N/mm ²
Elongation at break	25 – 50 %
Heat resistance	-20 °C to +70 °C
Ambient air temperature	+5 °C to +40 °C (heat the tape and the substrate below +10 °C during application)
Substrate temperature	+5 °C to +40 °C (heat the tape and the substrate below +10 °C during application)
Storability	72 months in dry, dark areas, at a temperature of +5 °C to +25 °C

SCH-SIKAMULTISEAL



PS Dusty grey

INDEX CHANGE	DATE	SIGNATURE		
MATERIAL BRAND			WEIGHT kg	SCALE
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD	SORTING NUMBER
AUXILIARY EQUIPMENT			NOTE	POSITION NUMBER
ELABORATED BY Ing. Kluska M.				
TESTED BY			OLD DRAWING	DRAWING NUMBER
TECHNOLOGIST				
NAME			SCH-SIKAMULTISEAL	
Sika bitumen sealing gray strip			Number of sheets	Sheet 

Created: 06.06.2026 17:40:18

Technical changes reserved