

TECHNICAL SHEET

SECONDARY BITUMINOUS WATERPROOFING LAYER

Bituminous underlay membrane for pitched roofs, with self-adhesive edge strips.

Designed for laying on timber decking. Vapour-tight bituminous underlay membrane and secondary waterproofing layer (PHI) with self-adhesive longitudinal joint, suitable for installation on timber decking or wood-based composite boards.

1 pcs roll = 40 m²



INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE		
SIZE, SEMI-FINISHED PRODUCTS			AUXILIARY EQUIPMENT		STN STANDARD	SORTING NUMBER	
ELABORATED BY Ing. Kluska M.			TESTED BY		NOTE	POSITION NUMBER	
TECHNOLOGIST		TECHNOLOGIST	OLD DRAWING		DRAWING NUMBER		
NAME Secondary bituminous waterproofing layer				Number of sheets		BAU S-TOP TS 40 NSK Sheet	

Created: 04.06.2026 09:29:50

Technical changes reserved

Technical parameter	
Top layer	synthetic fibre fleece with self-adhesive edge strips
Bottom layer	synthetic fibre fleece with self-adhesive edge strips
Support insert type	synthetic fibre fleece
Low temperature flexibility	≤ -25 °C
Resistance to elevated temperature	≥ +100 °C