

TECHNICAL SHEET

SECONDARY BITUMINOUS WATERPROOFING LAYER

BAU S-TOP UDS 1,5

Bituminous underlay membrane for pitched roofs, secondary waterproofing layer with self-adhesive edge strip, laying on timber decking.

Vapour-tight bituminous underlay membrane and secondary waterproofing layer with enhanced degree of tightness, featuring a self-adhesive joint. Exceptionally robust. Suitable for installation on timber decking or large-format wood-based composite boards.



1 pcs roll = 20 m²

Technical parameter	
Top layer	synthetic fibre fleece with self-adhesive edge strips
Bottom layer	synthetic fibre fleece with self-adhesive edge strips
Support insert type	synthetic fibre fleece
Low temperature flexibility	≤ -25 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER	
TESTED BY			TECHNOLOGIST		DRAWING NUMBER	
NAME			Secondary bituminous waterproofing layer		Number of sheets BAU S-TOP UDS 1,5 Sheet	

Created: 20.04.2026 07:25:17

Technical changes reserved