

TECHNICAL SHEET

SECONDARY BITUMINOUS WATERPROOFING LAYER

BAU S-TOP UDS 3

Bituminous underlay membrane for pitched roofs, secondary waterproofing layer with self-adhesive edge strip, laying on timber decking.

Vapour-tight bituminous underlay membrane and secondary waterproofing layer with enhanced degree of tightness, featuring a self-adhesive joint. Exceptionally robust. Suitable for installation on timber decking or large-format wood-based composite boards.



1 pcs roll = 10 m²

Technical parameter	
Top layer	synthetic fibre fleece with self-adhesive edge strips
Bottom layer	synthetic fibre fleece with self-adhesive edge strips
Support insert type	synthetic fibre fleece
Low temperature flexibility	≤ -20 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			AUXILIARY EQUIPMENT		STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.			TESTED BY		NOTE	POSITION NUMBER
TECHNOLOGIST		TECHNOLOGIST	OLD DRAWING		DRAWING NUMBER	
NAME Secondary bituminous waterproofing layer			Number of sheets		BAU S-TOP UDS 3	Sheet

Created: 20.04.2026 07:25:17

Technical changes reserved