

TECHNICAL SHEET

SELF-ADHESIVE BITUMINOUS VAPOUR BARRIER

BAU S-TEC DBR

High-quality, cold self-adhesive and airtight elastomer-modified bituminous vapour barrier membrane, compliant with all the fire safety requirements according to DIN 18234 (reduced fire load). With a width of 1.25 m, it is ideal for installation over trapezoidal steel sheet.

Cold self-adhesive elastomer-modified bituminous vapour barrier (low fire load).



1 pcs roll = 100 m²

Technical parameter	
Application method	cold bonding
Top layer	special aluminium foil
Bottom layer	removable foil, self-adhesive compound
Support insert type	aluminium-polyester composite reinforced with glass fabric
Low temperature flexibility	≤ -40 °C
Resistance to elevated temperature	≥ +110 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY	BAUDER	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER		
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER		
ELABORATED BY Ing. Kluska M.			TECHNOLOGIST		OLD DRAWING		DRAWING NUMBER
TESTED BY			NAME		Number of sheets		
			Self-adhesive bituminous vapour barrier		BAU S-TEC DBR Sheet		

Created: 03.06.2026 20:02:45

Technical changes reserved