

TECHNICAL SHEET

TOP BITUMINOUS MEMBRANE WITH NATURAL SLATE SURFACE

BAU S-EP 4 AF

Application area on top layer in multi-layer waterproofing systems for flat roofs.

Elastomer-modified (SBS) torch-on bituminous membrane.



1 pcs roll = 8 m²

Technical parameter	
Application method	by torching
Top layer	natural slate
Bottom layer	combustible foil
Support insert type	polyester fleece 160 g/m ²
Low temperature flexibility	≤ -20 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER	
TESTED BY			TECHNOLOGIST		DRAWING NUMBER	
NAME			Top bituminous membrane with natural slate surface		Number of sheets BAU S-EP 4 AF Sheet	

Created: 19.04.2026 14:01:15

Technical changes reserved