

TECHNICAL SHEET

# TOP BITUMINOUS MEMBRANE WITH NATURAL SLATE SURFACE

# BAU S-PYE PV 200 S4

Application area: top layer in multi-layer waterproofing systems for flat roofs.

Elastomer-modified (SBS) torch-on bituminous membrane.



1 pcs roll = 7,5 m<sup>2</sup>

Technical parameter	
Application method	by torching
Top layer	natural slate
Bottom layer	combustible foil
Support insert type	polyester fleece 250 g/m <sup>2</sup>
Low temperature flexibility	≤ -25 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	<b>BAUDER</b>	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER		
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER		
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER		
TESTED BY			TECHNOLOGIST		DRAWING NUMBER		
NAME			Top bituminous membrane with natural slate surface		Number of sheets BAU S-PYE PV 200 S4 Sheet		

Created: 19.04.2026 14:00:56

Technical changes reserved