

TECHNICAL SHEET

BOTTOM BITUMINOUS MEMBRANE WITH MINERAL SURFACING

BAU S-PYE PV 200 S4 M

Application area on support insert type in multi-layer waterproofing systems for flat roofs.

Elastomer-modified (SBS) torch-on bituminous membrane.



1 pcs roll = 10 m²

Technical parameter	
Application method	by torching
Top layer	fine granulate finish
Bottom layer	combustible foil
Support insert type	polyester fleece 250 g/m ²
Low temperature flexibility	≤ -25 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY	BAUDER	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER		
AUXILIARY EQUIPMENT			ELABORATED BY Ing. Kluska M.		NOTE		POSITION NUMBER
TESTED BY			TECHNOLOGIST		OLD DRAWING		DRAWING NUMBER
NAME			Bottom bituminous membrane with mineral surfacing		Number of sheets		BAU S-PYE PV 200 S4 M Sheet

Created: 06.03.2026 05:24:10

Technical changes reserved