

TECHNICAL SHEET

FPO/TPO THERMOPLAN FOIL 1,5 mm

BAU S-THERMOP T15 SS

High-quality synthetic roofing foil based on FPO-PP with synthetic fibre reinforcement.

Application area: single-layer roofing and waterproofing membrane for mechanically fastened flat roof systems or for waterproofing under load-bearing layers such as green roofs or gravel.



1 pcs roll = 30 m²

Technical parameter	
Application method	hot air
Top layer	mouse grey, similar to RAL 7001
Bottom layer	black
Support insert type	PES fabric
Thickness	1,5 mm

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			AUXILIARY EQUIPMENT		STN STANDARD	SORTING NUMBER
ELABORATED BY Ing. Kluska M.			TESTED BY		NOTE	POSITION NUMBER
TECHNOLOGIST		TECHNOLOGIST	OLD DRAWING		DRAWING NUMBER	
NAME FPO/TPO THERMOPLAN foil 1,5 mm				BAU S-THERMOP T15 SS Number of sheets _____ Sheet		

Created: 06.06.2026 17:59:27

Technical changes reserved