

TECHNICAL SHEET

FPO/TPO THERMOPLAN FOIL 1,5 mm

BAU S-THERMOP T15 SS

High-quality synthetic roofing foil based on FPO-PP with synthetic fibre reinforcement.

Application area: single-layer roofing and waterproofing membrane for mechanically fastened flat roof systems or for waterproofing under load-bearing layers such as green roofs or gravel.



1 pcs roll = 30 m²

Technical parameter	
Application method	hot air
Top layer	mouse grey, similar to RAL 7001
Bottom layer	black
Support insert type	PES fabric
Thickness	1,5 mm

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY®	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER	
TESTED BY			TECHNOLOGIST		DRAWING NUMBER	
NAME			FPO/TPO THERMOPLAN foil 1,5 mm		BAU S-THERMOP T15 SS Number of sheets Sheet	

Created: 06.06.2026 17:08:42

Technical changes reserved