

TECHNICAL SHEET

PVC FOIL 1,5 mm

Universal synthetic roofing membrane based on PVC-P with synthetic fibre reinforcement, with enhanced fire protection.

Single-layer roofing and waterproofing membrane for mechanically fastened flat roof systems or for waterproofing under load-bearing layers such as green roofs or gravel.

1 pcs roll = 30 m²

BAU S-THERMOFOL U15 AN



AN Anthracite – RAL 7016

Technical parameter	
Application method	hot air
Colour	anthracite, similar to RAL 7016
Bottom layer	dark grey
Support insert type	fabric made of synthetic PES fibres
Thickness	1,50 mm

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY	BAUDER	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER		
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER		
ELABORATED BY Ing. Kluska M.			TECHNOLOGIST		OLD DRAWING		DRAWING NUMBER
TESTED BY			NAME		BAU S-THERMOFOL U15 AN		
PVC foil 1,5 mm			Number of sheets		Sheet		

Created: 06.03.2026 06:57:42

Technical changes reserved