

TECHNICAL SHEET

PVC FOIL 1,5 mm

Universal synthetic roofing membrane based on PVC-P with synthetic fibre reinforcement, with enhanced fire protection.

Single-layer roofing and waterproofing membrane for mechanically fastened flat roof systems or for waterproofing under load-bearing layers such as green roofs or gravel.

1 pcs roll = 30 m²

BAU S-THERMOFOL U15 PS



PS Dusty grey – RAL 7037

| Technical parameter | |
|---------------------|-------------------------------------|
| Application method | hot air |
| Colour | dusty grey, similar to RAL 7035 |
| Bottom layer | dark grey |
| Support insert type | fabric made of synthetic PES fibres |
| Thickness | 1,50 mm |

| | | | | | | | |
|------------------------------|--------|------|-----------|-----------------------|---------------|--|--|
| INDEX | CHANGE | DATE | SIGNATURE | KJG QUALITY | BAUDER | Scan code for 3D model | |
| MATERIAL BRAND | | | W.C. | WEIGHT kg | | SCALE | |
| SIZE, SEMI-FINISHED PRODUCTS | | | | STN STANDARD | | SORTING NUMBER | |
| AUXILIARY EQUIPMENT | | | | NOTE | | POSITION NUMBER | |
| ELABORATED BY Ing. Kluska M. | | | | TECHNOLOGIST | | DRAWING NUMBER | |
| TESTED BY | | | | OLD DRAWING | | DRAWING NUMBER | |
| NAME | | | | PVC foil 1,5 mm | | BAU S-THERMOFOL U15 PS Number of sheets Sheet | |

Created: 20.04.2026 09:53:45

Technical changes reserved