

TECHNICAL SHEET

# PVC FOIL 1,5 mm

Universal synthetic roofing membrane based on PVC-P with synthetic fibre reinforcement, with enhanced fire protection.

Single-layer roofing and waterproofing membrane for mechanically fastened flat roof systems or for waterproofing under load-bearing layers such as green roofs or gravel.

1 pcs roll = 30 m<sup>2</sup>

# BAU S-THERMOFOL U15 PS



**PS** Dusty grey – RAL 7037

Technical parameter	
Application method	hot air
Colour	dusty grey, similar to RAL 7035
Bottom layer	dark grey
Support insert type	fabric made of synthetic PES fibres
Thickness	1,50 mm

INDEX	CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	<b>BAUDER</b>	Scan code for 3D model	
MATERIAL BRAND			W.C.	WEIGHT kg		SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER		
AUXILIARY EQUIPMENT			ELABORATED BY Ing. Kluska M.		NOTE		POSITION NUMBER
TESTED BY		TECHNOLOGIST		OLD DRAWING		DRAWING NUMBER	
NAME				PVC foil 1,5 mm		BAU S-THERMOFOL U15 PS Number of sheets Sheet	

Created: 04.06.2026 12:15:27

Technical changes reserved