

TECHNICAL SHEET

TOP BITUMINOUS MEMBRANE WITH GREY SLATE SURFACE

BAU S-K5K

Application area: top layer in multi-layer waterproofing systems for flat roofs.

Elastomer-modified (SBS) torch-on bituminous membrane.



1 pcs roll = 5 m²

Technical parameter	
Application method	by torching
Top layer	grey slate
Bottom layer	combustible foil
Support insert type	polyester fleece 250 g/m ²
Low temperature flexibility	≤ -35 °C
Resistance to elevated temperature	≥ +120 °C

INDEX	CHANGE	DATE	SIGNATURE	KJG QUALITY	BAUDER	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER	
TESTED BY			TECHNOLOGIST		DRAWING NUMBER	
NAME			Top bituminous membrane with grey slate surface		Number of sheets	
					BAU S-K5K Sheet	

Created: 04.06.2026 06:17:50

Technical changes reserved