

TECHNICAL SHEET

# ROOT-RESISTANT BITUMINOUS MEMBRANE

# BAU S-FLEX WF5

Asphalt membrane for waterproofing buildings against moisture and pressurized water.

Elastomer (SBS) modified meltable top asphalt membrane with root protection.



1 pcs roll = 8 m<sup>2</sup>

Technical parameter	
Application method	by torching
Top layer	green slate
Bottom layer	combustible foil
Support insert type	polyester fleece 250 g/m <sup>2</sup>
Low temperature flexibility	≤ -25 °C
Resistance to elevated temperature	≥ +100 °C

INDEX	CHANGE	DATE	SIGNATURE	<b>KJG</b> QUALITY	<b>BAUDER</b>	Scan code for 3D model
MATERIAL BRAND			W.C.	WEIGHT kg	SCALE	
SIZE, SEMI-FINISHED PRODUCTS			STN STANDARD		SORTING NUMBER	
AUXILIARY EQUIPMENT			NOTE		POSITION NUMBER	
ELABORATED BY Ing. Kluska M.			OLD DRAWING		DRAWING NUMBER	
TESTED BY			TECHNOLOGIST		DRAWING NUMBER	
NAME			Root-resistant bituminous membrane		Number of sheets	BAU S-FLEX WF5 Sheet

Created: 30.04.2026 02:23:51

Technical changes reserved