

TECHNICAL SHEET

METAL ROOFING UNI 1

W-UNI1



| Technical parameters [mm] | |
|---|-------------------------------|
| Covering width | 1105 |
| Total width | 1195 |
| Metal sheet thickness | 0,70 |
| Profile height (standard / non-standard) | 38 / 43 |
| Shaped rib height (standard / non-standard) | 15 / 20 |
| Module length (standard / non-standard) | 350 / 400 |
| Roof covering length | min. 480 – max. 8180 |
| Weight | approx. 5,0 kg/m ² |
| Folding length when dividing the covering | 110 |



BH Aluminium prepainted – White aluminium – RAL 9006

L – OPTIMAL LENGTH OF ROOFING FOR MODULE 350 mm



| number of modules | net length | minimum length L | interval for optimal length L | maximum length L |
|-------------------|------------|------------------|-------------------------------|------------------|
| 1 | 350 | 480 | = < L = | 700 |
| 2 | 700 | 830 | = < L = | 1050 |
| 3 | 1050 | 1180 | = < L = | 1400 |
| 4 | 1400 | 1530 | = < L = | 1750 |
| 5 | 1750 | 1880 | = < L = | 2100 |
| 6 | 2100 | 2230 | = < L = | 2450 |
| 7 | 2450 | 2580 | = < L = | 2800 |
| 8 | 2800 | 2930 | = < L = | 3150 |
| 9 | 3150 | 3280 | = < L = | 3500 |
| 10 | 3500 | 3630 | = < L = | 3850 |
| 11 | 3850 | 3980 | = < L = | 4200 |
| 12 | 4200 | 4330 | = < L = | 4550 |
| 13 | 4550 | 4680 | = < L = | 4900 |
| 14 | 4900 | 5030 | = < L = | 5250 |
| 15 | 5250 | 5380 | = < L = | 5600 |
| 16 | 5600 | 5730 | = < L = | 5950 |
| 17 | 5950 | 6080 | = < L = | 6300 |
| 18 | 6300 | 6430 | = < L = | 6650 |
| 19 | 6650 | 6780 | = < L = | 7000 |
| 20 | 7000 | 7130 | = < L = | 7350 |
| 21 | 7350 | 7480 | = < L = | 7700 |
| 22 | 7700 | 7830 | = < L = | 8050 |
| 23 | 8050 | 8180 | = < L = | 8400 |

L – OPTIMAL LENGTH OF ROOFING FOR MODULE 400 mm

| number of modules | net length | minimum length L | interval for optimal length L | maximum length L |
|-------------------|------------|------------------|-------------------------------|------------------|
| 1 | 400 | 530 | = < L = | 800 |
| 2 | 800 | 930 | = < L = | 1200 |
| 3 | 1200 | 1330 | = < L = | 1600 |
| 4 | 1600 | 1730 | = < L = | 2000 |
| 5 | 2000 | 2130 | = < L = | 2400 |
| 6 | 2400 | 2530 | = < L = | 2800 |
| 7 | 2800 | 2930 | = < L = | 3200 |
| 8 | 3200 | 3330 | = < L = | 3600 |
| 9 | 3600 | 3730 | = < L = | 4000 |
| 10 | 4000 | 4130 | = < L = | 4400 |
| 11 | 4400 | 4530 | = < L = | 4800 |
| 12 | 4800 | 4930 | = < L = | 5200 |
| 13 | 5200 | 5330 | = < L = | 5600 |
| 14 | 5600 | 5730 | = < L = | 6000 |
| 15 | 6000 | 6130 | = < L = | 6400 |
| 16 | 6400 | 6530 | = < L = | 6800 |
| 17 | 6800 | 6930 | = < L = | 7200 |
| 18 | 7200 | 7330 | = < L = | 7600 |
| 19 | 7600 | 7730 | = < L = | 8000 |
| 20 | 8000 | 8130 | = < L = | 8400 |

L – optimal length must be at least equal to or greater than the value in the left column of the table for production reasons. The minimum length after cutting the end is 100 mm and the maximum length 370 mm.

L – optimal length must be at least equal to or greater than the value in the left column of the table for production reasons. The minimum length after cutting the end is 100 mm and the maximum length 370 mm.



| | | | | | | | |
|------------------------------|--------|------|------------------|-----------------------|---------------------|------------------------|----------------|
| INDEX | CHANGE | DATE | SIGNATURE | KJG QUALITY | UNI 1 | Scan code for 3D model | QR CODE |
| MATERIAL BRAND | | | W.C. | WEIGHT kg | | SCALE | |
| SIZE, SEMI-FINISHED PRODUCTS | | | STN STANDARD | | SORTING NUMBER | | |
| AUXILIARY EQUIPMENT | | | NOTE | | POSITION NUMBER | | |
| ELABORATED BY Ing. Kluska M. | | | TECHNOLOGIST | | OLD DRAWING | | DRAWING NUMBER |
| TESTED BY | | | NAME | | Metal roofing UNI 1 | | |
| TECHNOLOGIST | | | Number of sheets | | W-UNI1 Sheet | | |

Created: 25.05.2026 03:43:23

Technical changes reserved