

TECHNICKÝ LIST

# ŽLABOVÝ KOTLÍK

# P-PKL



Rozměry [mm]

| Menovitá veľkosť | Ø d1 | Ø d2 | A   | B   | C      | D  | E  |
|------------------|------|------|-----|-----|--------|----|----|
| 200/60           | 60   | 80   | 115 | 80  | 99,5   | 30 | 12 |
| 250/60           | 60   | 105  | 140 | 100 | 127,5  | 30 | 12 |
| 250/80           | 80   | 105  | 140 | 120 | 117,5  | 40 | 12 |
| 280/80           | 80   | 127  | 165 | 120 | 143,5  | 40 | 12 |
| 280/100          | 100  | 127  | 165 | 120 | 142,5  | 45 | 14 |
| 333/80           | 80   | 153  | 185 | 140 | 176,5  | 40 | 14 |
| 333/100          | 100  | 153  | 185 | 140 | 170,0  | 45 | 14 |
| 333/120          | 120  | 153  | 185 | 140 | 171,50 | 50 | 14 |
| 400/100          | 100  | 192  | 210 | 160 | 205,0  | 45 | 14 |
| 400/120          | 120  | 192  | 210 | 160 | 200,4  | 51 | 14 |
| 400/150          | 150  | 192  | 240 | 168 | 205,0  | 45 | 14 |

**TM** Pozink lakovaný – Testa di Moro – RAL 8028

|           |                      |              |             |                        |                        |  |
|-----------|----------------------|--------------|-------------|------------------------|------------------------|--|
| INDEX     | ZMENA                | DATUM        | PODPIS      | <b>KJG</b><br>QUALITY® | Scan code for 3D model |  |
| ZN. MAT.  | ROZM.-POLOT          | T.O.         | HMOTNOSŤ kg |                        |                        |  |
| POM. ZAR. | VYPR. Ing. Kluska M. | STN          | POZN.       | TR.Č.                  | Č.POZÍCIE              |  |
| PRESK.    | TECHNOL.             | STARÝ V.     | Č.V.        |                        |                        |  |
| NÁZOV     | Žľabový kotlík       | Počet listov | P-PKL       | List                   |                        |  |

Vytvorené: 22.04.2026 04:23:59

Technické zmeny vyhradené